



HD 13 VT

HD 13 VT - Articulated combi roller with vibratory drum



- ▶ Optimum front view due to concaving front end
- ▶ Good visibility — optimum view of drum's outer edges
- ▶ Ergonomic driver platform
- ▶ Modern instrument panel
- ▶ Low machine height
- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Convenient maintenance and service



HD 13 VT

HD 13 VT - Articulated combi roller with vibratory drum



HD 13 VT

Weights		
Operating weight with ROPS	kg	3825
Operating weight, max.	kg	4790
Axle load, front/rear	kg	2005/1820
Load per tyre, rear	kg	455
Static linear load, front	kg/cm	15,5
French classific., data/class		10,5/VT0.PLO
Machine dimensions		
Max. working width	mm	1338
Lateral overhang, left/right	mm	63/63
Ground clearance, left/right	mm	720/720
Ground clearance, centre	mm	305
Turning radius, inside	mm	2690
Drum type, front		smooth/non-divided
Drum thickness, front	mm	17
Size of tyres, rear		10.5/80-16
Diesel engine		
Manufacturer		KUBOTA
Version		V2203
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		34,6/47,1/2700
Power rating SAE J1349, kW/HP/rpm		34,6/46,4/2700
Emissions standard EU/USA		III A / Tier 4i
Fuel tank, capacity	L	73
Drive		
Hydrostatic drive, front/rear		Wheel motor/Wheel motor
Speed, infinitely variable	km/h	0 - 11,0
Climbing ability, vibration on/off	%	30/40
Vibration		
Vibration frequency, front, I/II	Hz	60/51
Amplitude, front, I/II	mm	0,51/0,31
Centrifugal force, front, I/II	kN	64/39
Steering		
Steering, type		Articulated steering
Steering, actuation		hydrostatic, steering wheel
Steering angle +/-	°	33
Oscillation angle +/-	°	8
Sprinkler system		
Water sprinkler, type		Pressure
Actuation, water sprinkler		interval/manual
Water tank, capacity	L	285
Additive sprinkling, type		Pressure
Actuation, additive sprinkling		Push button
Additive tank, capacity	L	18

Equipment
Crab steering up to 50 mm, Spring-mounted driver's seat, Comfort seat with seat belt, Operating hours counter, Indicator lights, Emergency stop switch

Optional equipment
Comfort driver cab, 2 spotlights on ROPS, Back-up alarm, Rotating beacon, Special colour, Sun roof, Edge pressing and cutting equipment, Sound insulation

Total length	L	2860
Width	B	1426
Total height	H	2590
Wheel base	A	1950
Drum width	X	1300
Drum diameter	D	900
Width over tyres	Y	1276
Diameter of tyres	R	810
Height loading, min.	HI	1820

